

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A method of initializing devices connected to a communication bus by a host device, comprising:
 - (a) determining which devices, if any, are branded devices and which devices, if any, are unbranded devices by the host device;
if there are no branded devices,
 - (b) sending a first focus command by the host device to a first one of the devices connected to the communication bus as a focused device;
 - (c) in response to a probe command sent by the host device to the focused device, returning configuration information by the focused device; and
 - (d) branding the focused device by the host device based upon the confirmation information, wherein the host device is the only initiating device and wherein the communication bus is a half duplex communication bus having a single shared data channel.
2. (Previously Presented) A method as recited in claim 1, further comprising;
 - (e) sending a blur command by the host device to the branded device;
 - (f) converting the blur command to second focus command by the branded device;
 - (g) passing the second focus command to a second one of the devices connected to the communication bus as the focused device by the first branded device;
 - (h) in response to a second probe command sent by the host device to the focused device, returning configuration information by the focused device; and
 - (i) branding the focused device by the host device based upon the configuration information.
3. (Original) A method as recited in claim 2, further comprising;
 - (j) repeating (e) - (i) for the remainder of the devices connected to the communication bus.
4. (Original) A method as recited in claim 1, wherein the branding comprises;
setting a branded flag; and
assigning a brand ID.

5. (Original) A method as recited in claim 1, further comprising:
setting up a driver software corresponding to the branded device.

6. (Currently Amended) Computer program product executable by a processor for initializing devices connected to a communication bus by a host device, comprising:
computer code for determining which devices, if any, are branded devices and which devices, if any, are unbranded devices by the host device;
computer code for sending a first focus command by the host device to a first one of the devices connected to the communication bus as a focused device if there are no branded devices
computer code for ~~in response~~ responding to a probe command sent by the host device to the focused device, returning configuration information by the focused device;
computer code for branding the focused device by the host device based upon the confirmation information wherein the host device is the only initiating device and wherein the communication bus is a half duplex communication bus having a single shared data channel; and
computer readable medium for storing the computer code.

7. (Previously Presented) Computer program product as recited in claim 6, further comprising;
computer code for sending a blur command by the host device to the branded device;
computer code for converting the blur command to second focus command by the branded device;
computer code for passing the second focus command to a second one of the devices connected to the communication bus as the focused device by the first branded device;
computer code for returning configuration information by the focused device in response to a second probe command sent by the host device to the focused device; and
computer code for branding the focused device by the host device based upon the configuration information.

8. (Original) Computer program product as recited in claim 6, wherein the computer code for branding comprises;

computer code for setting a branded flag; and

computer code for assigning a brand ID.

9. (Currently Amended) Computer program product as recited in claim 6 ~~claim 1~~, further comprising:

computer code for a setting up a driver software corresponding to the branded device.

10. (Currently Amended) Any of a number of devices connected to a communication bus are initialized by a host device that sends a focus command to a first one of the unbranded devices which responds by returning configuration back to host device which, in turn, brands the responding device based upon the returned configuration information, wherein, once the device is branded, the host device ~~computer~~ brands a second one of the unbranded devices by sending a blur command to the branded device which converts the blur command to a second focus command which is passed by the branded device to the second one of the unbranded devices which responds by returning configuration information to the host device which, in turn, responds by branding the second device based upon the configuration information wherein the host device is the only initiating device and wherein the communication bus is a half duplex communication bus having a single shared data channel.